



KULITE SEMICONDUCTOR PRODUCTS, INC.
One Willow Tree Road - Leonia, NJ 07605
Tel: 201-461-0900 - Fax: 201-461-0990 - <http://www.Kulite.com>

PRESSURE TRANSDUCERS
PRESSURE TRANSMITTERS
ACCELEROMETERS
LOAD CELLS
SEMICONDUCTOR GAGES
INTEGRATED SENSORS

Date: November 7, 2016

Subject: Kulite Semiconductor Products, Inc. RoHS Declaration

After careful evaluation, Kulite Engineering has determined that Kulite's products are in compliance to the EU Directive 2011/65/EU RoHS (version dated 2011 June 8), Restriction of the use of certain Hazardous Substances in electrical and electronic equipment, and its amendments ("RoHS Directive").

The RoHS Directive does not apply to certain Kulite products sold for military and space applications and to products specifically designed for research and development and made available on a business to business bases. (See Article 2, Scope).

Kulite's products do not contain Mercury (Hg), Cadmium (Cd), Hexavalent Chromium (Cr+6), Poly Brominated Biphenyls (PBB), Poly Brominated Diphenyl Ethers (PBDE) including Deca-BDE, (Hexabromocyclododecane (HBCDD), Bis(2-ethylhexyl) phthalate (DEHP), Butyl benzyl phthalate (BBP), Dibutyl phthalate (DBP), and Diisobutyl phthalate (DIBP) above the tolerated maximum concentration values (MCV).

Leaded solder is the only restricted substance listed in the RoHS Directive that is used in Kulite products. However, it falls under one or more of the exemptions, specifically:

RoHS Directive
Annex III
Section 7(a)

Lead in high melting temperature type solders (i.e. lead-based alloys containing 85% by weight or more).

RoHS Directive
Annex III
Section 24

Lead in solders for the soldering to machined through hole discoidal and planar array ceramic multilayer capacitors.

Directive 2014/5/EU dated
October 18, 2013

- Lead in solders on printed circuit boards
- Termination coatings of electrical and electronic components and coatings of printed circuit boards
- Solders for connecting of wires and cables
- Solder connecting transducers and sensors that are used at temperatures under - 20 degrees C. All Kulite products are designed to operate under -20 degrees C.